



## SAFETY DATA SHEET

SUNOCO CFR

Page: 1

Compilation date: 22/11/2016

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** SUNOCO CFR

**Synonyms:** UNLEADED GASOLINE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC13: Fuels.

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** Anglo American Oil Company Ltd

58 Holton Road

Holton Heath Trading Park

Poole

Dorset

BH16 6LT

United Kingdom

**Tel:** 01929 551557

**Fax:** 01929 551567

**Email:** racing@aoil.co.uk

#### 1.4. Emergency telephone number

**Emergency tel:** +44(0)1929 551 557

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CLP:** Repr. 2: H361d; STOT RE 2: H373; Aquatic Chronic 2: H411; Carc. 1A: H350; Muta. 1B: H340; Skin Irrit. 2: H315; STOT SE 2: H371; Flam. Liq. 2: H225; Flam. Liq. 1: H224

**Most important adverse effects:** Extremely flammable liquid and vapour. Causes skin irritation. May cause genetic defects. May cause cancer. Suspected of damaging the unborn child. May cause damage to organs . May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

**Label elements:**

**Hazard statements:** H224: Extremely flammable liquid and vapour.

H315: Causes skin irritation.

H340: May cause genetic defects.

H350: May cause cancer.

H361d: Suspected of damaging the unborn child.

[cont...]

# SAFETY DATA SHEET

SUNOCO CFR

Page: 2

H371: May cause damage to organs .

H373: May cause damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

**Hazard pictograms:** GHS02: Flame

GHS08: Health hazard

GHS07: Exclamation mark

GHS09: Environmental



**Signal words:** Danger

**Precautionary statements:** P201: Obtain special instructions before use.

P273: Avoid release to the environment.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P264: Wash Hands thoroughly after handling.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233: Keep container tightly closed.

P240: Ground/Bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P243: Take precautionary measures against static discharge.

P242: Use only non-sparking tools.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P281: Use personal protective equipment as required.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+352: IF ON SKIN: Wash with plenty of water/.

P331: Do NOT induce vomiting.

P363: Wash contaminated clothing before reuse.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

[cont...]

# SAFETY DATA SHEET

SUNOCO CFR

Page: 3

## Hazardous ingredients:

### LOW BOILING POINT NAPHTHA - UNSPECIFIED - GASOLINE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
289-220-8	86290-81-5	-	Carc. 1B: H350; Muta. 1B: H340; Asp. Tox. 1: H304; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	30-50%

### LOW BOILING POINT MODIFIED NAPHTHA - NAPHTHA (PETROLEUM), LIGHT ALKYLATE

265-068-8	64741-66-8	-	Carc. 1B: H350; Muta. 1B: H340; Asp. Tox. 1: H304; Flam. Liq. 1: H224; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	10-30%
-----------	------------	---	---	--------

### TOLUENE

203-625-9	108-88-3	-	Flam. Liq. 2: H225; Repr. 2: H361d; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336	10-30%
-----------	----------	---	--	--------

### ETHANOL

200-578-6	64-17-5	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	1-10%
-----------	---------	--	--------------------	-------

### BUTANE

203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	----------	--	-------------------------------------	-------

### BENZENE

200-753-7	71-43-2	-	Flam. Liq. 2: H225; Carc. 1A: H350; Muta. 1B: H340; STOT RE 1: H372; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Skin Irrit. 2: H315	<1%
-----------	---------	---	---	-----

## Non-classified ingredients:

### XYLENE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	<1%

### ISOPENTANE

201-142-8	78-78-4	-	Flam. Liq. 1: H224; Asp. Tox. 1: H304; STOT SE 3: H336; Aquatic Chronic 2: H411; -: EUH066	<1%
-----------	---------	---	--	-----

[cont...]

# SAFETY DATA SHEET

SUNOCO CFR

Page: 4

## N-HEXANE

203-777-6	110-54-3	-	Flam. Liq. 2: H225; Repr. 2: H361f; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411	-
-----------	----------	---	--	---

## CYCLOPENTANE

206-016-6	287-92-3	-	Flam. Liq. 2: H225; Aquatic Chronic 3: H412	-
-----------	----------	---	--	---

## ETHYLBENZENE

202-849-4	100-41-4	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; STOT RE 2: H373; Asp. Tox. 1: H304	-
-----------	----------	---	---	---

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Transfer to hospital as soon as possible. Consult a doctor. Do not induce vomiting.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. If conscious, ensure the casualty sits or lies down. If unconscious and breathing is OK, place in the recovery position. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact. There may be redness or whiteness of the skin in the area of exposure.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Show this safety data sheet to the doctor in attendance. Do not induce vomiting.

## Section 5: Fire-fighting measures

[cont...]

# SAFETY DATA SHEET

SUNOCO CFR

Page: 5

## 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Use water spray to cool containers. Carbon dioxide. Dry chemical powder.

## 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Extremely flammable. Vapour may travel considerable distance to source of ignition and flash back. Forms explosive air-vapour mixture.

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Remove all incompatible materials as outlined in section 10 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid. Do not create dust. Evacuate the area immediately.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the neighbourhood to the presence of fumes or gas.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Wash the spillage site with large amounts of water. Avoid all incompatible materials in clean-up procedure - see section 10 of SDS. Transfer to a suitable container. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks. Mix with sand or vermiculite. Clean-up should be dealt with only by qualified personnel familiar with the specific substance. The fire brigade must be present at any clean-up operation of larger spills.

### 6.4. Reference to other sections

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area. Ensure there is exhaust ventilation of the area. Do not handle in a confined space. Earth any equipment used in handling.

[cont...]

# SAFETY DATA SHEET

SUNOCO CFR

Page: 6

Smoking is forbidden. Use non-sparking tools. Avoid direct contact with the substance.

Pipes used to transfer the product must be free of water.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed. Keep away from direct sunlight. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Ensure a retention tank is installed. Avoid incompatible materials and conditions - see section 10 of SDS.

**Suitable packaging:** Steel drums.

## 7.3. Specific end use(s)

**Specific end use(s):** PC13: Fuels.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**TOLUENE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	191 mg/m <sup>3</sup>	384 mg/m <sup>3</sup>	-	-

**ETHANOL**

UK	1920 mg/m <sup>3</sup>	-	-	-
----	------------------------	---	---	---

**BUTANE**

UK	1450 mg/m <sup>3</sup>	1810 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

**BENZENE**

UK	1 ppm	-	-	-
----	-------	---	---	---

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure there is exhaust ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition. Ensure a retention tank is installed. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Respiratory protective device with particle filter. Half face filtering respirator (EN140). Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves. Nitrile gloves. Breakthrough time of the glove material > 8 hours.

**Eye protection:** Safety glasses with side-shields. Ensure eye bath is to hand.

[cont...]

# SAFETY DATA SHEET

SUNOCO CFR

Page: 7

**Skin protection:** Solvent resistant protective clothing. Protective clothing, antistatic. Ensure safety shower is to hand.

**Environmental:** Refer to specific Member State legislation for requirements under Community environmental legislation. An environmental assessment must be made to ensure compliance with local environmental legislation. Ensure a retention tank is installed. The floor of the storage room must be impermeable to prevent the escape of liquids. Ensure all engineering measures mentioned in section 7 of SDS are in place. Storage should be placed inside a fully bunded area of sufficient size to contain the volume plus 10%. Prevent from entering in public sewers or the immediate environment. Ensure emissions from ventilation or equipment comply with environmental protection legislation.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Colourless

**Odour:** Characteristic odour

**Boiling point/range°C:** 38

**Flash point°C:** -40

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Flames. Sources of ignition. Shock. Hot surfaces. Direct sunlight.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids. Alkalis. Acids. Halogens. Chlorine, Hydrogen Peroxide, Concentrated Oxygen

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

[cont...]

# SAFETY DATA SHEET

SUNOCO CFR

Page: 8

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

##### LOW BOILING POINT NAPHTHA - UNSPECIFIED - GASOLINE

ORL	MUS	LD50	60	ml/kg
ORL	RAT	LD50	92	gm/kg

##### TOLUENE

IVN	RAT	LD50	1960	mg/kg
ORL	MUS	LD50	2	gm/kg
ORL	RAT	LD50	6900	mg/kg

##### ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

##### BENZENE

ORL	MUS	LD50	4700	mg/kg
ORL	RAT	LD50	930	mg/kg
SKN	MUS	LD50	48	mg/kg

##### XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

##### N-HEXANE

IPR	RAT	LDLO	9100	mg/kg
IVN	MUS	LDLO	831	mg/kg
ORL	RAT	LD50	25	gm/kg

##### CYCLOPENTANE

ORL	MUS	LD50	12800	mg/kg
ORL	RAT	LD50	11400	mg/kg

[cont...]



# SAFETY DATA SHEET

SUNOCO CFR

Page: 9

## ETHYLBENZENE

IPR	MUS	LD50	2624	µl/kg
ORL	RAT	LD50	3500	mg/kg

### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Germ cell mutagenicity	--	Hazardous: calculated
Carcinogenicity	--	Hazardous: calculated
Reproductive toxicity	--	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact. There may be redness or whiteness of the skin in the area of exposure.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** Bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Highly volatile. Floats on water. Vapour is heavier than air. Absorbed only slowly into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Toxic to flora. Toxic to fauna. Toxic to soil organisms. Toxic to aquatic organisms.

## Section 13: Disposal considerations

[cont...]

# SAFETY DATA SHEET

SUNOCO CFR

Page: 10

## 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Recovery operations:** Not applicable.

**Waste code number:** 13 07 02

**Disposal of packaging:** Dispose of as normal industrial waste. Retain for recovery.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1203

### 14.2. UN proper shipping name

**Shipping name:** GASOLINE

### 14.3. Transport hazard class(es)

**Transport class:** 3

### 14.4. Packing group

**Packing group:** II

### 14.5. Environmental hazards

**Environmentally hazardous:** Yes

**Marine pollutant:** Yes

### 14.6. Special precautions for user

**Tunnel code:** D/E

**Transport category:** 2

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H224: Extremely flammable liquid and vapour.

H225: Highly flammable liquid and vapour.

[cont...]

# SAFETY DATA SHEET

SUNOCO CFR

Page: 11

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H350: May cause cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H361d: Suspected of damaging the unborn child.

H361f: Suspected of damaging fertility.

H371: May cause damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H372: Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.