



SAFETY DATA SHEET

SUNOCO FR

Page: 1

Compilation date: 23/11/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SUNOCO FR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC13: Fuels.

1.3. Details of the supplier of the safety data sheet

Company name: Anglo American Oil Company Ltd

58 Holton Road

Holton Heath Trading Park

Poole

Dorset

BH16 6LT

United Kingdom

Tel: 01929 551557

Fax: 01929 551567

Email: racing@aaoil.co.uk

1.4. Emergency telephone number

Emergency tel: +44(0)1929 551 557

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Muta. 1B: H340; STOT RE 2: H373; Aquatic Chronic 2: H411; Carc. 1A: H350; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT SE 3: H336

Most important adverse effects: Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects.

H350: May cause cancer.

H361d: Suspected of damaging the unborn child.

[cont...]

SAFETY DATA SHEET

SUNOCO FR

Page: 2

H373: May cause damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard

GHS09: Environmental



Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

2.3. Other hazards

Other hazards: Danger of serious damage to health by prolonged exposure.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TOLUENE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-625-9	108-88-3	-	Flam. Liq. 2: H225; Repr. 2: H361d; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336	10-30%

LOW BOILING POINT MODIFIED NAPHTHA - NAPHTHA (PETROLEUM), LIGHT ALKYLATE

265-068-8	64741-66-8	-	Carc. 1B: H350; Muta. 1B: H340; Asp. Tox. 1: H304; Flam. Liq. 1: H224; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	10-30%
-----------	------------	---	---	--------

[cont...]

SAFETY DATA SHEET

SUNOCO FR

Page: 3

LOW BOILING POINT NAPHTHA - GASOLINE, NATURAL

232-349-1	8006-61-9	-	Carc. 1B: H350; Muta. 1B: H340; Asp. Tox. 1: H304; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	10-30%
-----------	-----------	---	---	--------

ETHANOL

200-578-6	64-17-5	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	1-10%
-----------	---------	---	--------------------	-------

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	-----------	---	--	-------

LOW BOILING POINT MODIFIED NAPHTHA - RAFINATES (PETROLEUM), CATALYTIC REFORMER ETHYLENE GLYCOL-WATER

270-088-5	68410-71-9	-	Carc. 1B: H350; Muta. 1B: H340; Asp. Tox. 1: H304; Flam. Liq. 1: H224; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	1-10%
-----------	------------	---	---	-------

BUTANE

203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	----------	---	-------------------------------------	-------

CYCLOHEXANE

203-806-2	110-82-7	-	Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	<1%
-----------	----------	---	--	-----

N-HEXANE

203-777-6	110-54-3	-	Flam. Liq. 2: H225; Repr. 2: H361f; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411	<1%
-----------	----------	---	--	-----

BENZENE

200-753-7	71-43-2	-	Flam. Liq. 2: H225; Carc. 1A: H350; Muta. 1B: H340; STOT RE 1: H372; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Skin Irrit. 2: H315	<1%
-----------	---------	---	--	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor. Do not induce vomiting. If conscious, give half a litre of water to drink immediately.

[cont...]

SAFETY DATA SHEET

SUNOCO FR

Page: 4

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. Alcohol resistant foam. Dry chemical powder. Carbon dioxide. Water spray.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes. Highly flammable. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Evacuate the area immediately.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the neighbourhood to the presence of fumes or gas.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

[cont...]

SAFETY DATA SHEET

SUNOCO FR

Page: 5

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Steel drums.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

TOLUENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	191 mg/m ³	384 mg/m ³	-	-

ETHANOL

UK	1920 mg/m ³	-	-	-
----	------------------------	---	---	---

XYLENE

UK	220 mg/m ³	441 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

BUTANE

UK	1450 mg/m ³	1810 mg/m ³	-	-
----	------------------------	------------------------	---	---

CYCLOHEXANE

UK	350 mg/m ³	1050 mg/m ³	-	-
----	-----------------------	------------------------	---	---

N-HEXANE

UK	72 mg/m ³	-	-	-
----	----------------------	---	---	---

BENZENE

UK	1 ppm	-	-	-
----	-------	---	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

[cont...]

SAFETY DATA SHEET

SUNOCO FR

Page: 6

Skin protection: Impermeable protective clothing.

Environmental: The floor of the storage room must be impermeable to prevent the escape of liquids.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Boiling point/range°C: 38

Flash point°C: -40

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

TOLUENE

IVN	RAT	LD50	1960	mg/kg
ORL	MUS	LD50	2	gm/kg
ORL	RAT	LD50	6900	mg/kg

[cont...]

SAFETY DATA SHEET

SUNOCO FR

Page: 7

ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

CYCLOHEXANE

ORL	MUS	LD50	813	mg/kg
ORL	RAT	LD50	12705	mg/kg

N-HEXANE

IPR	RAT	LDLO	9100	mg/kg
IVN	MUS	LDLO	831	mg/kg
ORL	RAT	LD50	25	gm/kg

BENZENE

ORL	MUS	LD50	4700	mg/kg
ORL	RAT	LD50	930	mg/kg
SKN	MUS	LD50	48	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Germ cell mutagenicity	--	Hazardous: calculated
Carcinogenicity	--	Hazardous: calculated
Reproductive toxicity	--	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

[cont...]

SAFETY DATA SHEET

SUNOCO FR

Page: 8

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Not applicable.

Waste code number: 13 07 02

Disposal of packaging: Dispose of as normal industrial waste. Retain for recovery.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3475

14.2. UN proper shipping name

Shipping name: GASOLINE

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

[cont...]

SAFETY DATA SHEET

SUNOCO FR

Page: 9

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.
H224: Extremely flammable liquid and vapour.
H225: Highly flammable liquid and vapour.
H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H312: Harmful in contact with skin.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H336: May cause drowsiness or dizziness.
H340: May cause genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H350: May cause cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H361d: Suspected of damaging the unborn child.
H361f: Suspected of damaging fertility.
H372: Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

[cont...]

SAFETY DATA SHEET

SUNOCO FR

Page: 10

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.