**R 5SR PLUS** 



Page: 1

Compilation date: 23/11/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product name: R 5SR PLUS

Synonyms: LEADED GASOLINE

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC13: Fuels.

## 1.3. Details of the supplier of the safety data sheet

Company name: Anglo American Oil Company Ltd

58 Holton Road Holton Heath Trading Park Poole Dorset BH16 6LT United Kingdom Tel: 01929 551557 Fax: 01929 551567 Email: racing@aaoil.co.uk

# 1.4. Emergency telephone number

Emergency tel: +44(0)1929 551 557

# Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification under CLP:	Aquatic Chronic 2: H411; Carc. 1A: H350; Flam. Liq. 2: H225; Muta. 1B: H340; Skin Irrit. 2:
	H315
Most important adverse effects:	Highly flammable liquid and vapour. Causes skin irritation. May cause genetic defects.
	May cause cancer. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

Label elements:

Laber elements.	
Hazard statements:	H225: Highly flammable liquid and vapour.
	H315: Causes skin irritation.
	H340: May cause genetic defects.
	H350: May cause cancer.
	H411: Toxic to aquatic life with long lasting effects.
Hazard pictograms:	GHS02: Flame
	GHS07: Exclamation mark

**R 5SR PLUS** 

Page: 2

GHS08: Health hazard GHS09: Environmental Signal words: Danger Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P241: Use explosion-proof electrical/ventilating/lighting/.. equipment. P240: Wear protective gloves/protective clothing/eye protection/face protection. P302+352: IF ON SKIN: Wash with plenty of water/. P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P308+313: IF exposed or concerned: Get medical attention.

Other hazards: Danger of serious damage to health by prolonged exposure.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

## 3.2. Mixtures

#### Hazardous ingredients:

#### LOW BOILING POINT NAPHTHA - UNSPECIFIED - GASOLINE

EINECS CAS PBT / WEL CLP Classification	Percent
289-220-8         86290-81-5         -         Carc. 1B: H350; Muta. 1B: H           Tox. 1: H304; Skin Irrit. 2: H3         -         Aguatic Chronic 2: H411	, I

### TERT-BUTYL METHYL ETHER

216-653-1 1634-04-4 -	Flam. Lig. 2: H225; Skin Irrit. 2: H315	1-10%

#### LOW BOILING POINT NAPHTHA - GASOLINE, NATURAL

232-349-1	8006-61-9	-	Carc. 1B: H350; Muta. 1B: H340; Asp.	1-10%
		Tox. 1: H304; Skin Irrit. 2: H315;		
			Aquatic Chronic 2: H411	

# R 5SR PLUS

# **Page:** 3

BENZENE				
200-753-7	71-43-2	- Flam. Liq. 2: H225; Carc. 1A: H350; Muta. 1B: H340; STOT RE 1: H372; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Skin Irrit. 2: H315	<1%	
TOLUENE				
203-625-9	108-88-3	- Flam. Liq. 2: H225; Repr. 2: H361d; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336	<1%	
tion 4: First a	aid measures			
.1. Description	n of first aid mea	easures		
		Remove all contaminated clothes and footwear immediately unless stuck to skin.		
		Drench the affected skin with running water for 10 minutes or longer if substance is s	still	
		on skin. Consult a doctor.		
	Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.		
	Ingestion:	Wash out mouth with water. Consult a doctor. Do not induce vomiting. If conscious, g	give	
		half a litre of water to drink immediately.		
	Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a	а	
		doctor.		
.2. Most impor	tant symptoms	s and effects, both acute and delayed		
	Skin contact:	There may be mild irritation at the site of contact.		
	Eye contact:	There may be irritation and redness.		
	Ingestion:	There may be irritation of the throat.		
	Inhalation:	No symptoms.		
Delayed / imme	ediate effects:	Delayed effects can be expected after long-term exposure.		
.3. Indication o	of any immedia	ate medical attention and special treatment needed		
mediate / spec	cial treatment:	Not applicable.		
tion 5: Fire-fi	ighting measu	Jres		
.1. Extinguishi	ng media			
Extingu	uishing media:	Suitable extinguishing media for the surrounding fire should be used. Use water spra	ау	
		to cool containers. Alcohol resistant foam. Dry chemical powder. Carbon dioxide. Wa	ater	
		spray.		
.2. Special haz	ards arising fre	rom the substance or mixture		
Ехро	sure hazards:	In combustion emits toxic fumes. Highly flammable. Forms explosive air-vapour mixt	ure.	
		Vapour may travel considerable distance to source of ignition and flash back.		

### R 5SR PLUS

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Evacuate the area immediately.

#### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the neighbourhood to the presence of fumes or gas.

6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

## 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

#### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Steel drums.

7.3. Specific end use(s)

Specific end use(s): No data available.

### Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

#### **TERT-BUTYL METHYL ETHER**

#### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	183.5 mg/m3	367 mg/m3	-	-

#### BENZENE

UK	1 ppm	-	-	-
----	-------	---	---	---

R 5SR PLUS

						Page:	5	
TOLUENE								
UK	1	91 mg/m3	384 mg/m3	-		-		
	DNEL/PNEC Values							
DNEL/FINEC Va								
	DNEL / PNEC	No data availa	able.					
8.2. Exposure	8.2. Exposure controls							
Engineer	ring measures:	Ensure there	is sufficient ventilation of	the area. Ensure lighting ar	nd electrical			
		equipment are	e not a source of ignition					
Respirat	ory protection:	Self-contained	d breathing apparatus m	ust be available in case of e	mergency.			
Ha	and protection:	Impermeable	gloves.					
E	Eye protection:	Safety glasse	s. Ensure eye bath is to	hand.				
S	kin protection:	Impermeable	protective clothing.					
E	Environmental:	The floor of th	e storage room must be	impermeable to prevent the	escape of liquids.			
Section 9: Physi	ical and chem	ical propertie	es					
9.1. Information	n on basic phys	ical and chem	nical properties					
	State:	•						
		Colourless						
Boiling	point/range°C:	Characteristic	; odoul	Elash poi	nt°C: -40			
		30			<b>III C.</b> -40			
9.2. Other infor	mation							
Oth	er information:	No data availa	able.					
Section 10: Stat	bility and react	ivity						
10.1. Reactivity	1							
	Reactivity:	Stable under	recommended transport	or storage conditions.				
10.2. Chemical	stability							
Che	mical stability:	Stable under	normal conditions. Stable	e at room temperature.				
10.3. Possibilit	y of hazardous	reactions						
			actions will not occur up	ler normal transport or stora	age conditions			
nazaru				e to conditions or materials				
10.4. Condition	is to avoid	Decompositio						
		Heat Hot sur	faces. Sources of ignitior	Flames				
		Hout Hot Sull						
10.5. Incompat	ible materials							

Materials to avoid: Strong oxidising agents. Strong acids.

# R 5SR PLUS

### **Page:** 6

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

#### Section 11: Toxicological information

#### 11.1. Information on toxicological effects

# Hazardous ingredients:

## LOW BOILING POINT NAPHTHA - UNSPECIFIED - GASOLINE

ORL	MUS	LD50	60	ml/kg
ORL	RAT	LD50	92	gm/kg

#### BENZENE

ORL	MUS	LD50	4700	mg/kg
ORL	RAT	LD50	930	mg/kg
SKN	MUS	LD50	48	mg/kg

# TOLUENE

IVN	RAT	LD50	1960	mg/kg
ORL	MUS	LD50	2	gm/kg
ORL	RAT	LD50	6900	mg/kg

#### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Germ cell mutagenicity		Hazardous: calculated
Carcinogenicity		Hazardous: calculated

### Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

# Section 12: Ecological information

### 12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

#### **R 5SR PLUS**

Page: 7

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

### 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

## 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

#### Other adverse effects: Negligible ecotoxicity.

## Section 13: Disposal considerations

13.1. Waste treatment methods

 Disposal operations:
 Transfer to a suitable container and arrange for collection by specialised disposal company.

 Recovery operations:
 Not applicable.

 Waste code number:
 13 07 02

 Disposal of packaging:
 Dispose of as normal industrial waste. Retain for recovery.

 NB:
 The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

# Section 14: Transport information

14.1. UN number

UN number: UN1203

#### 14.2. UN proper shipping name

Shipping name: GASOLINE

#### 14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

R 5SR PLUS

# Section 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# Specific regulations: Not applicable.

## 15.2. Chemical Safety Assessment

# Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# Section 16: Other information

Other information	
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H225: Highly flammable liquid and vapour.
	H304: May be fatal if swallowed and enters airways.
	H315: Causes skin irritation.
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
	H340: May cause genetic defects <state conclusively="" exposure="" if="" is="" it="" of="" proven="" route="" th="" that<=""></state>
	no other routes of exposure cause the hazard>.
	H350: May cause cancer <state conclusively="" exposure="" if="" is="" it="" no="" of="" other<="" proven="" route="" th="" that=""></state>
	routes of exposure cause the hazard>.
	H361d: Suspected of damaging the unborn child.
	H372: Causes damage to organs <or affected,="" all="" if="" known="" organs="" state=""> through</or>
	prolonged or repeated exposure <state conclusively="" exposure="" if="" is="" it="" of="" proven="" route="" th="" that<=""></state>
	no other routes of exposure cause the hazard>.
	H373: May cause damage to organs <or affected,="" all="" if="" known="" organs="" state=""> through</or>
	prolonged or repeated exposure <state conclusively="" exposure="" if="" is="" it="" of="" proven="" route="" th="" that<=""></state>
	no other routes of exposure cause the hazard>.
	H411: Toxic to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.