

R E85-R

Page: 1

Compilation date: 09/04/2018

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: R E85-R

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC13: Fuels.

1.3. Details of the supplier of the safety data sheet

Company name: Anglo American Oil Company Ltd

58 Holton Road

Holton Heath Trading Park

Poole
Dorset
BH16 6LT

United Kingdom **Tel:** 01929 551557

Fax: 01929 551567

Email: racing@aaoil.co.uk

1.4. Emergency telephone number

Emergency tel: +44(0)1929 551 557

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Repr. 2: H361d; Aquatic Chronic 3: H412; Flam. Liq. 2: H225; Skin Irrit. 2: H315

Most important adverse effects: Highly flammable liquid and vapour. Causes skin irritation. Suspected of damaging the

unborn child. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H361d: Suspected of damaging the unborn child.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS08: Health hazard







R E85-R

Page: 2

Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241: Use explosion-proof equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

P308+P313: IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Other hazards: Highly flammable. Hygroscopic: readily absorbs water from air. Harmful in contact with

skin. Harmful if swallowed. Toxic by inhalation. Irritating to eyes. Irritating to respiratory

system. Irritating to skin.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-578-6	64-17-5	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	70-90%

LOW BOILING POINT MODIFIED NAPHTHA - NAPHTHA (PETROLEUM), FULL-RANGE ALKYLATE, BUTANE-CONTAINING

271-26	7-0 68527-27-5	-	Asp. Tox. 1: H304; Flam. Liq. 1: H224; Skin Irrit. 2: H315; Aquatic Chronic 2:	1-10%
			H411	

TOLUENE

203-625-9	108-88-3	-	Flam. Liq. 2: H225; Repr. 2: H361d;	1-10%
			Asp. Tox. 1: H304; STOT RE 2: H373;	
			Skin Irrit. 2: H315; STOT SE 3: H336	

METHANOL

200-659-6	67-56-1	-	Flam. Liq. 2: H225; Acute Tox. 3: H331;	<1%
			Acute Tox. 3: H311; Acute Tox. 3: H301;	
			STOT SE 1: H370	

Contains: The Ethanol / Methanol content in the mixture is from UK TSDA 9 specification denatured ethanol.

Section 4: First aid measures

R E85-R

Page: 3

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If

unconscious, check for breathing and apply artificial respiration if necessary. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely. The vision may

become blurred.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Dry chemical

powder. Carbon dioxide. Alcohol resistant foam. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. Forms explosive air-vapour mixture. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of

ignition. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the

escape of liquid.

R E85-R

Page: 4

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Earth any equipment used in handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Keep away from direct sunlight. Prevent the build up of electrostatic

charge in the immediate area.

Suitable packaging: Steel drums.

7.3. Specific end use(s)

Specific end use(s): PC13: Fuels.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

TOLUENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	191 mg/m3	384 mg/m3	-	-

METHANOL

UK	266 mg/m3	222 ma/m2		
UN	266 mg/m3	333 Hg/H3	<u>-</u>	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure there is exhaust ventilation of

R E85-R

Page: 5

the area. Ensure lighting and electrical equipment are not a source of ignition. Ensure

all engineering measures mentioned in section 7 of SDS are in place.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing. Antistatic boots. Ensure safety shower is to hand. **Environmental:** Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Alcoholic

Evaporation rate: Slow

Oxidising: No data available.

Solubility in water: Slightly soluble

Viscosity: No data available.

Boiling point/range°C: 57-82 Melting point/range°C: Not applicable.

Flammability limits %: lower: 1.5 upper: 7.6

Flash point°C: -40 Autoflammability°C: 280

Vapour pressure: 5-16 pH: Not applicable.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Bases. Acids. Halogens. Chorine, Hydrogen Peroxide,

Concentrated Oxygen

R E85-R

Page: 6

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

TOLUENE

IVN	RAT	LD50	1960	mg/kg
ORL	MUS	LD50	2	gm/kg
ORL	RAT	LD50	6900	mg/kg

METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Reproductive toxicity		Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely. The vision may

become blurred.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

R E85-R

Page: 7

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3475

14.2. UN proper shipping name

Shipping name: ETHANOL AND GASOLINE MIXTURE

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

R E85-R

Page: 8

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H224: Extremely flammable liquid and vapour.

H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed.

H304: May be fatal if swallowed and enters airways.

H311: Toxic in contact with skin.

H315: Causes skin irritation.

H331: Toxic if inhaled.

H336: May cause drowsiness or dizziness.

H361d: Suspected of damaging the unborn child.

H370: Causes damage to organs ({{{0|||message=<or state all organs affected, if known>|||filter=(_)?ORGAN_.+}}}) ({{{1|||message=<state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>|||filter=(_)? EXP_ROUTE_.+}}}).

H373: May cause damage to organs ({{{0|||message=<or state all organs affected, if known>|||filter=(_)?ORGAN_.+}}}) through prolonged or repeated exposure ({{{1|||} message=<state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>|||filter=(_)?EXP_ROUTE_.+}}}).

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.