



COMMERCIAL TRUCKING



AUTOMOTIVE



MOBILE ELECTRONICS



OFF-ROAD OHV / UTV



POWERSPORTS



PERSONAL WATERCRAFT



MARINE



RECREATIONAL VEHICLES



# Full Throttle Series

HIGH-PERFORMANCE AGM BATTERIES

Full Throttle AGM batteries provide a combination of power, stability, and built-in resilience to keep you running in the most extreme conditions.



HIGH CRANKING



LONG LIFE



MAINTENANCE-FREE



CORROSION-FREE



TPPL TECHNOLOGY



NON-HAZARDOUS



SPILL-PROOF



WEATHER RESISTANT



CLEAN-GREEN

FT MODEL	GROUP SIZE	CCA	PHCA	HCA	CA	CAP. C20 (AH)	RES. CAP. @ 25A (min)	POSITIVE TERM. POSITION	TERM. TYPE	DIMENSIONS (in / mm)				WEIGHT (lbs / kg)
										LENGTH	WIDTH	HEIGHT	TTL HEIGHT	
FT100	BTX9-BS	100	310	200	155	8	8	LHP	M6	5.43 (138)	3.39 (86)	4.02 (102)	4.02 (102)	71 (3.2)
FT185	BS16L-B	185	545	300	240	14	15	RHP	M6	6.97 (177)	3.39 (86)	5.16 (131)	5.16 (131)	10.8 (4.9)
FT200	BTX20L-BS	200	535	300	265	14	20	RHP	M6M	6.69 (170)	3.90 (99)	6.18 (157)	6.18 (157)	13.2 (6.0)
FT200L	BTX20H-BS	200	535	300	265	14	20	LHP	M6M	6.69 (170)	3.90 (99)	6.18 (157)	6.18 (157)	13.2 (6.0)
FT230	BT19BL-BS	230	680	410	310	20	28	RHP	M6	7.13 (181)	3.03 (77)	6.57 (167)	6.57 (167)	15.4 (7.0)
FT230-D	BT19BL-BS	180	500	290	240	22	22	RHP	M6	7.13 (181)	3.03 (77)	6.57 (167)	6.57 (167)	13.9 (6.3)
FT265	B16CL-B	265	625	440	350	18	26	RHP	M6	6.69 (170)	3.90 (99)	6.89 (175)	6.89 (175)	15.7 (7.1)
FT410	-	410	925	625	530	28	48	RHP	M6 + TP26	6.50 (165)	6.93 (176)	4.92 (125)	5.67 (144)**	23.2 (10.5)
FT410L	BTX30L	410	925	625	530	28	48	LHP	M6 + TP26	6.50 (165)	6.93 (176)	4.92 (125)	5.67 (144)**	23.2 (10.5)
FT438-U1	U1	438	975	605	525	35	50	LHP	M6 + TP26	7.72 (196)	5.16 (131)	6.57 (167)	7.56 (192)**	25.1 (11.4)
FT438-U1R	U1R/46A24L	438	975	605	525	35	50	RHP	M6 + TP26	7.72 (196)	5.16 (131)	6.57 (167)	7.57 (192)**	25.1 (11.4)
FT560	26R	560	1200	860	725	44	80	RHP	M6 + TP26	7.80 (198)	6.54 (166)	6.69 (170)	7.09 (180)**	33.3 (15.1)
FT560L	26	560	1200	860	725	44	80	LHP	M6 + TP26	7.80 (198)	6.54 (166)	6.69 (170)	7.09 (180)**	33.3 (15.1)
FT610-47	47/L2/H5	610	1280	890	745	50	105	RHP	AP	9.49 (241)	6.89 (175)	7.48 (190)	7.48 (190)	42.1 (19.1)
FT620-51	51	620	1300	890	745	55	100	LHP	M8 + TP28	9.02 (229)	5.43 (138)	8.19 (208)	9.06 (230)**	40.3 (18.3)
FT680-48	48/L3/H6	680	1320	975	810	60	120	RHP	AP	10.94 (278)	6.89 (175)	7.48 (190)	7.48 (190)	47.8 (21.7)
FT750-25	25	750	1400	1080	900	64	120	LHP	AP	9.45 (240)	6.85 (174)	7.95 (202)	8.66 (220)	48.1 (21.8)
FT750-35	35/34R	750	1400	1080	900	64	120	RHP	AP	9.45 (240)	6.85 (174)	7.95 (202)	8.66 (220)	48.1 (21.8)
FT825-24*	24	825	1500	1200	1000	65	135	LHP	M8 + TP28	10.28 (261)	6.77 (172)	8.19 (208)	8.90 (226)**	46.0 (20.9)
FT825-34	34	825	1500	1200	1000	65	135	LHP	M8 + TP28	10.28 (261)	6.77 (172)	7.19 (182)	8.19 (208)**	46.0 (20.9)
FT825-78	34/78	825	1500	1200	1000	65	135	LHP	M8 + FR45	10.28 (261)	6.77 (172)	7.19 (182)	8.31 (211)	46.0 (20.9)
FT890-49	49/L5/H8	890	1800	1300	1070	80	168	RHP	AP	13.90 (353)	6.89 (175)	7.24 (184)	7.48 (190)	60.4 (27.4)
FT930-65	65	930	1750	1350	1070	75	142	LHP	M8 + TP28	11.81 (300)	7.17 (182)	6.65 (169)	7.24 (184)**	54.9 (24.5)
FT965-27	27	965	1950	1380	1170	100	205	LHP	DT	12.09 (307)	6.65 (169)	8.43 (214)	9.33 (237)	69.5 (31.5)
FT1100-31	31A	1100	2200	1560	1360	110	230	RHP	M8 + TP28	12.99 (330)	6.81 (173)	8.31 (211)	9.33 (237)**	75.2 (34.1)
FT1100-31ST	31T	1100	2200	1560	1360	110	230	RHP	3/8" Stud	12.99 (330)	6.81 (173)	8.43 (214)	9.13 (232)	75.2 (34.1)
FT1150-6T	6TL	1150	2250	1700	1450	120	273	RHP	M8 + TP28	11.02 (280)	10.43 (265)	8.09 (206)	8.86 (225)**	85.8 (38.9)
FT1210	GC12	1210	2400	1750	1505	140	321	LHP	M8	12.87 (327)	7.17 (182)	10.59 (269)	10.75 (273)	98.1 (44.5)
FT1250-40LT	40LT/D5	1250	2200	1720	1500	175	340	LHP	M8 + TP28	20.20 (513)	8.78 (223)	7.75 (197)	8.74 (222)**	123.5 (56.0)
FT1450-8D	8D	1450	2400	1950	1700	225	450	RHP	M8 + TP28	20.35 (517)	10.79 (274)	8.58 (218)	9.57 (243)**	161.2 (73.1)
FT16V830-24	24 (16V)	660	1140	990	830	62	120	LHP	M6	10.24 (260)	6.61 (168)	8.39 (213)	8.54 (217)	59.3 (26.9)

\* FT825-34 with 1" spacer

\*\* Brass SAE post is removable reducing total height by 0.86" to 1.00"